

Hole ID	Collar Easting	Collar Northing	Collar RL	Collar Dip	Collar Azimuth	Block	From (m)	To (m)	Downhole Interval (m)	Au Grade (g/t)	Grade x Downhole Interval (gm/t)	ETT* (m)	Cutoff (Au g/t)
OKWR21-002	273022	702699	66.202	-60	270	1	52.0	62.0	10.0	1.74	17	8.7	0.3
inc							53.0	56.0	3.0	4.83	14	2.6	1.5
OKWR21-003	272750	702599	83.064	-60	270	1	48.0	68.0	20.0	0.51	10	17.3	0.3
OKWR21-004A	272699	702595	84.425	-60	270	1	0.0	17.0	17.0	1.14	19	14.7	0.3
OKWR21-007	272724	701794	128.579	-60	90	4	7.0	74.0	67.0	2.12	142	58.0	0.3
inc							11.0	25.0	14.0	7.59	106	12.1	1.5
inc							32.0	42.0	10.0	2.19	22	8.7	1.5
OKWR21-008	272688	701795	133.495	-60	90	4	4.0	54.0	50.0	2.25	113	43.3	0.3
inc							5.0	11.0	6.0	3.31	20	5.2	1.5
inc							19.0	26.0	7.0	8.20	57	6.1	1.5
OKWR21-009	272655	701793	140.287	-60	90	4	35.0	72.0	37.0	2.44	90	32.0	0.3
inc							37.0	48.0	11.0	3.45	38	9.5	1.5
inc							51.0	60.0	9.0	3.60	32	7.8	1.5
inc							66.0	70.0	4.0	2.14	9	3.5	1.5
OKWR21-010	272695	701270	131.657	-60	270	4	15.0	63.0	48.0	0.46	22	41.6	0.3
OKWR21-011	272736	701279	134.302	-60	270	4	48.0	63.0	15.0	0.36	5	13.0	0.3
OKWR21-013	272767	701458	88.117	-60	240	4	1.0	62.0	61.0	0.62	38	52.8	0.3
OKWR21-014	272731	701453	88.498	-60	240	4	21.0	89.0	68.0	3.29	224	58.9	0.3
inc							21.0	24.0	3.0	4.74	14	2.6	1.5
inc							47.0	59.0	12.0	10.96	132	10.4	1.5
inc							67.0	78.0	11.0	4.83	53	9.5	1.5
OKWR21-015	272702	701450	88.787	-60	240	4	30.0	40.0	10.0	1.23	12	8.7	0.3
inc							31.0	34.0	3.0	2.28	7	2.6	1.5
OKWR21-015	272702	701450	88.787	-60	240	4	52.0	90.0	38.0	2.58	98	32.9	0.3
inc							69.0	88.0	19.0	4.44	84	16.5	1.5
OKWR21-016	272700	701608	101.179	-60	90	4	1.0	58.0	57.0	2.21	126	49.4	0.3
inc							5.0	38.0	33.0	3.00	99	28.6	1.5
OKWR21-018	272682	701899	147.408	-60	270	4	62.0	73.0	11.0	0.78	9	9.5	0.3
OKWR21-019	272698	701902	144.94	-60	270	4	12.0	37.0	25.0	5.01	125	21.7	0.3
inc							14.0	30.0	16.0	7.43	119	13.9	1.5
OKWR21-020	272739	701901	133.903	-60	270	4	12.0	60.0	48.0	1.36	65	41.6	0.3
inc							44.0	48.0	4.0	4.04	16	3.5	1.5
inc							53.0	60.0	7.0	4.85	34	6.1	1.5
OKWR21-028	272744	701993	133.546	-60	270	4	5.0	77.0	72.0	0.44	32	62.4	0.3
inc							40.0	45.0	5.0	1.85	9	4.3	1.5
inc							71.0	75.0	4.0	1.68	7	3.5	1.5
OKWR21-034	272559	701548	121.106	-60	254	4	52.0	66.0	14.0	0.31	4	12.1	0.3
OKWR21-035	272516	701542	121.136	-60	270	4	3.0	30.0	27.0	0.67	18	23.4	0.3
OKWR21-038	272752	701791	125.989	-60	90	4	21.0	52.0	31.0	14.92	463	26.8	0.3
inc							31.0	37.0	6.0	74.61	448	5.2	1.5
OKWR21-040	272734	701168	104.166	-60	240	5	14.0	38.0	24.0	1.10	26		0.3
inc							15.0	18.0	3.0	5.28	16		1.5
OKWR21-041	272700	701162	98.702	-60	254	5	1.0	16.0	15.0	0.47	7		0.3
OKWR21-041	272700	701162	98.702	-60	254	5	27.0	51.0	24.0	0.54	13		0.3
OKWR21-041	272700	701162	98.702	-60	254	5	69.0	80.0	11.0	0.38	4		0.3
OKWR21-042	272656	701143	96.875	-60	240	5	57.0	80.0	23.0	0.46	10		0.3
OKWR21-043	272644	701138	86.783	-60	240	5	31.0	62.0	31.0	0.36	11		0.3
OKWR21-044	272613	701116	85.064	-60	240	5	3.0	18.0	15.0	0.61	9		0.3
OKWR21-045	272729	701118	82.559	-60	240	5	11.0	27.0	16.0	0.31	5		0.3
OKWR21-045	272729	701118	82.559	-60	240	5	55.0	78.0	23.0	0.38	9		0.3
OKWR21-049	272566	700627	77.218	-60	240	6	3.0	39.0	36.0	0.37	13		0.3
OKWR21-050	272640	700628	75.531	-60	240	6	55.0	69.0	14.0	0.74	10		0.3
inc							64.0	69.0	5.0	1.58	8		1.5
OKWR21-056	272741	702100	136.301	-60	270	1	10.0	28.0	18.0	3.83	69	15.6	0.3
inc							18.0	26.0	8.0	8.06	64	6.9	1.5
OKWR21-056	272741	702100	136.301	-60	270	1	42.0	52.0	10.0	0.38	4	8.7	0.3
OKWR21-057	272783	702123	128.366	-60	270	1	45.0	56.0	11.0	0.41	5	9.5	0.3
OKWR21-058	272715	702192	135.797	-60	270	1	20.0	65.0	45.0	0.85	38	39.0	0.3
inc							33.0	37.0	4.0	2.43	10	3.5	1.5
OKWR21-059	272754	702198	126.56	-60	270	1	68.0	80.0	12.0	0.85	10	10.4	0.3
inc							75.0	78.0	3.0	2.49	7	2.6	1.5
OKWR21-072	272778	702336	100.154	-60	240	1	96.0	109.0	13.0	0.81	11	11.3	0.3
OKWR21-073	272750	702499	78.421	-60	270	1	1.0	4.0	3.0	3.12	9	2.6	1.5
OKWR21-073	272750	702499	78.421	-60	270	1	45.0	62.0	17.0	0.78	13	14.7	0.3
inc							58.0	62.0	4.0	2.04	8	3.5	1.5
OKWR21-076	272923	701753	84.723	-60	270	4	80.0	83.0	3.0	2.73	8	2.6	1.5
OKWR21-081	272641	700949	78.85	-60	270	6	18.0	54.0	36.0	1.05	38		0.3
inc							31.0	39.0	8.0	3.14	25		1.5
OKWR21-082	272683	700810	75.644	-50	240	6	46.0	117.0	71.0	0.31	22		0.3
OKWR21-083	272632	700639	75.392	-50	240	6	65.0	86.0	21.0	1.26	26		0.3

Hole ID	Collar Easting	Collar Northing	Collar RL	Collar Dip	Collar Azimuth	Block	From (m)	To (m)	Downhole Interval (m)	Au Grade (g/t)	Grade x Downhole Interval (gm/t)	ETT* (m)	Cutoff (Au g/t)
OKWR21-086	272672	700578	78.081	-60	240	6	42.0	80.0	38.0	0.36	14		0.3
OKWR21-087	272697	700584	72.831	-60	240	6	59.0	70.0	11.0	0.33	4		0.3
OKWR21-092	272675	700346	109.812	-60	240	6	1.0	38.0	37.0	0.41	15		0.3
OKWR21-093	272707	700361	100.768	-60	240	6	0.0	11.0	11.0	1.22	13		0.3
inc							0.0	5.0	5.0	2.27	11		1.5
OKWR21-093	272707	700361	100.768	-60	240	6	40.0	53.0	13.0	0.31	4		0.3
OKWR21-094	272631	700209	120.073	-60	270	6	1.0	29.0	28.0	0.38	11		0.3
OKWR21-096	272707	700232	99.954	-60	270	6	25.0	38.0	13.0	1.07	14		0.3
OKWR21-096	272707	700232	99.954	-60	270	6	56.0	80.0	24.0	0.41	10		0.3
OKWR21-099	272761	701704	108.271	-60	270	4	3.0	118.0	115.0	3.64	419	99.6	0.3
inc							36.0	52.0	16.0	18.98	304	13.9	1.5
inc							66.0	76.0	10.0	3.75	38	8.7	1.5
inc							105.0	108.0	3.0	3.71	11	2.6	1.5
OKWR21-100	272694	701693	119.21	-60	360	4	0.0	100.0	100.0	1.24	124	86.6	0.3
inc							14.0	22.0	8.0	3.33	27	6.9	1.5
inc							28.0	32.0	4.0	1.85	7	3.5	1.5
inc							39.0	42.0	3.0	12.37	37	2.6	1.5
OKWR21-101	272711	701789	129.367	-60	180	4	10.0	59.0	49.0	1.99	98	42.4	0.3
inc							10.0	13.0	3.0	5.32	16	2.6	1.5
inc							37.0	45.0	8.0	7.75	62	6.9	1.5
inc							51.0	54.0	3.0	1.68	5	2.6	1.5
OKWR21-101	272711	701789	129.367	-60	180	4	73.0	120.0	47.0	2.50	118	40.7	0.3
inc							75.0	80.0	5.0	16.00	80	4.3	1.5
OKWR21-103	272691	702398	105.261	-60	270	1	78.0	84.0	6.0	3.74	22	5.2	1.5
OKWR21-104	272716	702427	91.859	-60	270	1	2.0	36.0	34.0	1.13	39	29.4	0.3
inc							19.0	24.0	5.0	6.16	31	4.3	1.5
OKWR22-120	272731	702456	92.661	-60	270	1	25.0	53.0	28.0	2.26	63	24.2	0.3
inc							48.0	51.0	3.0	18.07	54	2.6	1.5
OKWR22-123	272705	702248	132.699	-60	270	1	2.0	19.0	17.0	4.97	85	14.7	0.3
inc							2.0	18.0	16.0	5.21	83	13.9	1.5
OKWR22-125	272743	702048	137.028	-60	270	1	21.0	77.0	56.0	0.66	37	48.5	0.3
OKWR22-127	272718	701944	139.473	-60	270	4	7.0	52.0	45.0	1.14	51	39.0	0.3
inc							24.0	31.0	7.0	2.26	16	6.1	1.5
inc							43.0	52.0	9.0	2.04	18	7.8	1.5
OKWR22-128	272725	701851	135.007	-60	270	4	2.0	75.0	73.0	3.52	257	63.2	0.3
inc							14.0	25.0	11.0	7.46	82	9.5	1.5
inc							32.0	57.0	25.0	6.09	152	21.7	1.5
inc							69.0	74.0	5.0	2.30	11	4.3	1.5
OKWR22-129	272697	701847	138.509	-60	270	4	2.0	34.0	32.0	1.88	60	27.7	0.3
inc							10.0	17.0	7.0	3.24	23	6.1	1.5
inc							23.0	32.0	9.0	3.20	29	7.8	1.5
OKWR22-131	272925	702547	79.987	-87	1	1	31.0	41.0	10.0	0.31	3	1.0	0.3
OKWR22-134	272729	702355	98.719	-60	270	1	30.0	44.0	14.0	2.56	36	12.1	0.3
inc							34.0	38.0	4.0	6.49	26	3.5	1.5
OKWR22-136	272708	702353	109.909	-60	270	1	0.0	24.0	24.0	1.42	34	20.8	0.3
inc							1.0	5.0	4.0	5.91	24	3.5	1.5
OKWR22-137	272722	702162	139.165	-60	270	1	25.0	52.0	27.0	0.74	20	23.4	0.3
OKWR22-158	272715	702292	115.323	-57	261	1	2.0	27.0	25.0	1.03	26	22.7	0.3
inc							16.0	23.0	7.0	2.37	17	5.9	1.5
OKWR22-159	272643	702394	120.229	-56	265	1	17.0	27.0	10.0	1.34	13	9.3	0.3
inc							18.0	22.0	4.0	2.60	10	3.3	1.5
OKWR22-160	272706	701851	136.934	-56	282	4	11.0	49.0	38.0	5.33	203	35.1	0.3
inc							11.0	22.0	11.0	12.94	142	9.2	1.5
inc							33.0	45.0	12.0	4.37	52	10.0	1.5
OKWR22-162	272750	701850	130.878	-55	276	4	13.0	80.0	67.0	1.80	121	62.9	0.3
inc							13.0	18.0	5.0	4.69	23	4.1	1.5
inc							36.0	39.0	3.0	2.17	7	2.5	1.5
inc							48.0	54.0	6.0	5.88	35	4.9	1.5
inc							59.0	62.0	3.0	1.51	5	2.5	1.5
inc							66.0	69.0	3.0	1.94	6	2.5	1.5
inc							72.0	80.0	8.0	2.27	18	6.6	1.5
OKWR22-163	272698	701746	124.466	-55	273	4	2.0	50.0	48.0	1.10	53	45.1	0.3
inc							2.0	8.0	6.0	1.95	12	4.9	1.5
inc							21.0	25.0	4.0	2.99	12	3.3	1.5
inc							45.0	48.0	3.0	3.77	11	2.5	1.5
OKWR22-164	272662	701513	81.477	-60	268	4	3.0	19.0	16.0	2.06	33	13.7	0.3
inc							7.0	16.0	9.0	3.40	31	7.8	1.5
OKWR22-165	272639	701346	130.048	-59	268	4	32.0	75.0	43.0	0.65	28	38.1	0.3
OKWR22-166	272647	701286	136.533	-56	274	4	63.0	77.0	14.0	0.57	8	12.9	0.3
OKWR22-167	272607	701220	118.121	-57	281	5	2.0	12.0	10.0	2.13	21		0.3

Hole ID	Collar Easting	Collar Northing	Collar RL	Collar Dip	Collar Azimuth	Block	From (m)	To (m)	Downhole Interval (m)	Au Grade (g/t)	Grade x Downhole Interval (gm/t)	ETT* (m)	Cutoff (Au g/t)
<i>inc</i>							4.0	8.0	4.0	3.82	15		1.5
OKWR22-168	272625	701176	98.6	-56	282	5	2.0	14.0	12.0	0.60	7		0.3
OKWR22-169	272643	701054	79.603	-58	272	5	36.0	66.0	30.0	0.47	14		0.3
OKWR22-170	272600	701026	89.637	-57	281	5	2.0	7.0	5.0	2.11	11		1.5
OKWR22-173	272650	701401	105.334	-59	269	4	0.0	29.0	29.0	0.94	27	25.4	0.3
<i>inc</i>							0.0	7.0	7.0	2.27	16	6.0	1.5
OKWR22-194	272555	701597	137.687	-58	268	4	51.0	64.0	13.0	0.64	8	11.7	0.3
OKWR22-198	272481	701407	133.173	-60	270	4	50.0	60.0	10.0	0.34	3	8.7	0.3
OKWR22-201	272558	701171	104.37	-60	270	5	14.0	47.0	33.0	0.90	30		0.3
<i>inc</i>							14.0	20.0	6.0	4.10	25		1.5
OKWR22-202	272568	701075	103.22	-60	270	5	56.0	70.0	14.0	0.79	11		0.3
OKWR22-204	272556	700877	111.601	-60	270	6	24.0	77.0	53.0	0.53	28		0.3
<i>inc</i>							56.0	60.0	4.0	1.79	7		1.5
OKWR22-205	272560	700823	116.335	-60	270	6	0.0	37.0	37.0	2.99	111		0.3
<i>inc</i>							0.0	12.0	12.0	5.30	64		1.5
<i>inc</i>							18.0	24.0	6.0	3.15	19		1.5
<i>inc</i>							29.0	33.0	4.0	3.88	16		1.5
OKWR22-206	272531	700780	120.12	-60	270	6	14.0	43.0	29.0	0.87	25		0.3
<i>inc</i>							17.0	21.0	4.0	4.88	20		1.5
OKWR22-209	272529	700723	98.458	-58	274	6	27.0	43.0	16.0	0.33	5		0.3
OKWR22-209	272529	700723	98.458	-58	274	6	55.0	71.0	16.0	0.48	8		0.3
OKWR22-210	272584	700711	76.585	-60	265	6	1.0	50.0	49.0	1.92	94		0.3
<i>inc</i>							3.0	6.0	3.0	1.79	5		1.5
OKWR22-211	272532	700675	85.389	-60	267	6	9.0	19.0	10.0	0.75	8		0.3
OKWR22-215	272619	700370	120.12	-59	265	6	60.0	74.0	14.0	0.48	7		0.3
OKWR22-220	272625	699935	74.78	-62	264	7	45.0	63.0	18.0	0.67	12		0.3
OKWR22-240	272902	697667	154.89	-58	272	8	8.0	32.0	24.0	0.33	8		0.3
OKWR22-246	272660	702494	93.16	-61	266	1	29.0	34.0	5.0	4.68	23	4.3	1.5
OKWR22-246	272660	702494	93.16	-61	266	1	53.0	71.0	18.0	0.59	11	15.4	0.3
OKWR22-250	272516	701070	124.101	-57	272	5	22.0	36.0	14.0	0.90	13		0.3
<i>inc</i>							22.0	26.0	4.0	2.58	10		1.5
OKWR22-252	272638	701170	98.331	-60	277	5	23.0	37.0	14.0	0.31	4		0.3
OKWR22-253	272636	701173	98.436	-58	149	5	19.0	53.0	34.0	0.74	25		0.3
<i>inc</i>							27.0	32.0	5.0	1.58	8		1.5
OKWR22-253	272636	701173	98.436	-58	149	5	64.0	102.0	38.0	0.57	22		0.3
OKWR22-254	272708	701153	98.382	-60	152	5	38.0	55.0	17.0	0.36	6		0.3
OKWR22-255	272620	701142	87.114	-58	276	5	2.0	18.0	16.0	0.53	9		0.3
OKWR22-257	272614	701105	86.275	-58	152	5	1.0	22.0	21.0	0.98	20		0.3
<i>inc</i>							2.0	5.0	3.0	4.38	13		1.5
OKWR22-269	272467	700579	109.614	-59	271	6	38.0	71.0	33.0	0.52	17		0.3
<i>inc</i>							47.0	51.0	4.0	2.06	8		1.5
OKWR22-273	272577	699921	89.411	-59	270	7	66.0	70.0	4.0	2.07	8		1.5
OKWR22-275	272633	699582	119.323	-59	270	7	7.0	44.0	37.0	1.21	45		0.3
<i>inc</i>							17.0	20.0	3.0	3.45	10		1.5
OKWR22-280	273380	696764	90.719	-59	269	8	58.0	70.0	12.0	0.56	7		0.3
OKWR22-309	272808	698797	82.321	-60	270	7	24.0	35.0	11.0	0.80	9		0.3
OKWR23-1006	269090	702780	123.994	-60	270	0	14.0	31.0	17.0	1.71	29		0.3
<i>inc</i>							14.0	19.0	5.0	4.08	20		1.5
OKWR23-1414	270307	702306	321.683	-60	90	HR	58.0	61.0	3.0	8.75	26.24		1.5

* Estimated True Thickness ("ETT") based on an average dip / dip direction of -65° / 095° to represent the orientation of the mineralized zone in Block 4. ETT only calculated for Blocks 1 and 4.

** Significant intervals calculated using a 0.3 g/t Au cutoff, 10m minimum length and 10m maximum consecutive internal waste. Included intervals calculated using a 1.5 g/t Au cutoff, 3m minimum length and a 2m maximum consecutive internal waste.